



Type	ELOPHY 80-6
Thrust Capacity (KG / N)	80 / 800
Thrust Stroke (MM)	60
Input Supply*	415V/3Ø/ 50Hz
Oil Capacity (Ltr)**	4.5

Notes:

1. Operating position of thruster must be within 10° of the vertical.
2. Supply leads must be flexible and allow thruster to pivot.

*Thruster can also be supply with different voltage and frequency as per customer requirements.
 ** Oil should be use Transformer Oil BS 148.

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN MILLIMETERS
 SURFACE FINISH:
 TOLERANCES:
 LINEAR:
 ANGULAR:

FINISH:

 DEBURR AND
 BREAK SHARP
 EDGES

DO NOT SCALE DRAWING
 REVISION
Speedage Engineers (India) Pvt. Ltd.

NAME	SIGNATURE	DATE	CONTACT
DRAWN Himanshu Tiwari			
CHK'D			
APPV'D J.A. Raichandani			9810173991
MFG			
Q.A			

TITLE:
**ELOPHY THRUSTER
 JET-4**
 DWG NO.

THIS DRAWING IS THE PROPERTY OF **SPEEDAGE ENGINEERS (INDIA) PVT. LTD.** & MUST NEITHER BE COPIED NOR BE MADE KNOWN TO ANY OTHER PARTY WITHOUT THEIR PRIOR WRITTEN CONSENT.

MATERIAL:

 WEIGHT:

SAE/DWG/JET4/80-6/01
 SCALE:1:4
 SHEET 1 OF 1
 A4