



Type	EMT-1/ ST 520
Thrust Capacity (Kg)	18
Thrust stroke (mm)	51
Input Watts	90
Input Supply*	415V/ 3 $\phi$ / 50Hz
Oil Capacity (Ltr.)**	2
Weight (Kg)	14

**Notes:**

1. Operating position of thruster must be within 10° of the vertical.
2. Supply leads must be flexible and allow thruster to pivot.

\* Thruster can also be supply with differant voltage and frequency as per customer requirments.  
 \*\* Oil should be use Transformer Oil BS 148.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: LINEAR: ANGULAR:		FINISH:	DEBURR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING	REVISION
					Speedage Engineers (India) Pvt. Ltd.	
				TITLE: <b>EMT 1/ST 520</b>		
NAME		SIGNATURE	DATE	CONTACT	DWG NO.	
DRAWN Himanshu Tiwari					SAE/DWG/TH18/01	
CHKD					A4	
APPV'D J.A. Raichandani				9810173991	SCALE:1:5	
MFG					SHEET 1 OF 1	
Q.A		MATERIAL:		WEIGHT:		
THIS DRAWING IS THE PROPERTY OF <b>SPEEDAGE ENGINEERS (INDIA) PVT. LTD.</b> & MUST NEITHER BE COPIED NOR BE MADE KNOWN TO ANY OTHER PARTY WITHOUT THEIR PRIOR WRITTEN CONSENT.						