



Type	EMT-2/ ST 535
Thrust Capacity (Kg)	34
Thrust stroke (mm)	51
Input Watts	150
Input Supply*	415V/ 3 $\phi$ / 50Hz
Oil Capacity (Ltr.)**	2.5
Weight (Kg)	25

**Notes:**

- Operating position of thruster must be within 10° of the vertical.
- Supply leads must be flexible and allow thruster to pivot.

- \* Thruster can also be supply with differant voltage and frequency as per customer requirments.
- \*\* Oil should be use Transformer Oil BS 148.

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN MILLIMETERS  
SURFACE FINISH:  
TOLERANCES:  
LINEAR:  
ANGULAR:

FINISH:

DEBURR AND  
BREAK SHARP  
EDGES

DO NOT SCALE DRAWING

REVISION

Speedage Engineers (India) Pvt. Ltd.

	NAME	SIGNATURE	DATE	CONTACT
DRAWN	Himanshu Tiwari			
CHK'D				
APPV'D	J.A. Raichandani			9810173991
MFG				

TITLE:

EMT-2/ ST 535

Q.A

MATERIAL:

DWG NO.

SAE/DWG/TH34/01

A4

THIS DRAWING IS THE PROPERTY OF **SPEEDAGE ENGINEERS (INDIA) PVT. LTD.** & MUST NEITHER BE COPIED NOR BE MADE KNOWN TO ANY OTHER PARTY WITHOUT THEIR PRIOR WRITTEN CONSENT.

WEIGHT:

SCALE:1:5

SHEET 1 OF 1