



| Type | EMT-4/ ST 870 |
|-----------------------|-----------------------|
| Thrust Capacity (Kg) | 68 |
| Thrust stroke (mm) | 76 |
| Input Watts | 200 |
| Input Supply* | 415V/ 3 ϕ / 50Hz |
| Oil Capacity (Ltr.)** | 4.5 |
| Weight (Kg) | 35 |

Notes:

1. Operating position of thruster must be within 10° of the vertical.
2. Supply leads must be flexible and allow thruster to pivot.

- * Thruster can also be supply with differant voltage and frequency as per customer requirments.
- ** Oil should be use Transformer Oil BS 148.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN MILLIMETERS
SURFACE FINISH:
TOLERANCES:
LINEAR:
ANGULAR:

FINISH:

DEBURR AND
BREAK SHARP
EDGES

DO NOT SCALE DRAWING

REVISION

Speedage Engineers (India) Pvt. Ltd.

| NAME | SIGNATURE | DATE | contact |
|---------------------------|-----------|------|------------|
| DRAWN Er. Himanshu Tiwari | | | |
| CHKD | | | |
| APPV'D J.A. Raichandani | | | 9810173991 |
| MFG | | | |

TITLE:

EMT-4/ ST 870

Q.A
THIS DRAWING IS THE PROPERTY OF **SPEEDAGE ENGINEERS (INDIA) PVT. LTD.** & MUST NEITHER BE COPIED NOR BE MADE KNOWN TO ANY OTHER PARTY WITHOUT THEIR PRIOR WRITTEN CONSENT.

MATERIAL:

DWG NO.

SAE/DWG/TH68/01

A4

WEIGHT:

SCALE:1:10

SHEET 1 OF 1